

TO DRAIN COOLING SYSTEM REMOVE RADIATOR CAP & OPEN DRAIN COCK AT:

1-BOTTOM RIGHT SIDE OF RADIATOR

2-LOWER RIGHT SIDE OF CRANKCASE

CAUTION! DO NOT EXCEED!

MAXIMUM ROAD SPEED IN MPH

TRANSMISSION	TRANSFER CASE	
	HIGH	LOW
FIFTH OVERDRIVE	56	28
FOURTH	44	22
THIRD	27	14
SECOND	16	8
FIRST	9	5
REVERSE	9	5

FRONT TRANSMISSION

TRANSFER CASE

HIGH UP

LOW DOWN

WARNING

DO NOT SHIFT TRANSFER CASE TO LOW WHEN VEHICLE SPEED IS OVER

FIFTH	28	MPH
FOURTH	22	MPH
THIRD	14	MPH
SECOND	8	MPH
FIRST	5	MPH
REVERSE	5	MPH

JDS SILVER/BLACK \$20

WEIGHT & DIMENSION DATA, TRUCK, CARGO 2-1/2 TON, 6X6, M35 A2, WO/W, IDENTIFICATION DATA

CG LOCATION BASED ON 5000 LB PAYLOAD W/O CREW

112 1/16 REDUCIBLE TO 79 11/16

WEIGHTS W/O CREW	EMPTY	CROSS C'TRY	HIGH WAY
PAYLOAD	5930	5000	10000
FRONT AXLE	5935	6126	6320
INTER AXLE	3535	5937	8340
REAR AXLE	3535	5937	8340
TOTAL POUNDS	13,000	18,000	23,000
MAX TOWED LOAD (PINTLE TOWED)	6000 LBS.	10000 LBS.	
SHIPPING SHIPPING CUBAGE	1,189 CU. FT.		

STOCK NO. 2320-077-1616

IDENTIFICATION NO.

MFD. BY KAISER JEEP CORPORATION SOUTH BEND INDIANA

CONTRACT NO. DAAE-06-68-C-007

U.S. PROPERTY

DURABLACK \$15

SERVICING DATA		TRUCK, 2 1/2 TON 6X6			PUBLICATIONS APPLYING TO THIS MACHINE
ELECTRICAL SYSTEM	24V	TIRE INFLATION PRESSURES	11:00 SINGLE	9:00 DUALS	
CRANKCASE CAPACITY	22 - QTS.	HIGHWAY 50 LBS. 50 LBS. CROSS COUNTRY 35 LBS. MUD, SAND, SNOW 15 LBS.	2 1/2 TON-5-TON	PAYLOAD	
COOLING SYSTEM	32 - QTS.		2 1/2 TON-5-TON	2 1/2 TON-5-TON	
FUEL TANK	50 - GAL.				
TEMPERATURE ABOVE 32° F	ENGINE OIL OE GRADE S.A.E 30	GEAR OIL GO GRADE 90	(GREASE SEE LUBRICATION ORDER NO. L09-2320-209-12)		
40° F TO -10° F	OE GRADE S.A.E. 40	GO GRADE 90			
0° F TO 65° F	SEE LUBRICATION ORDER NO. L09-2320-209-12				

AUTHORIZED FUELS

VV - F - 800 (DIESEL)
 MIL - F - 46005 (CIE)
 MIL - 6 - 3056 (GASOLINE)
 MIXING FUELS PERMISSABLE

CAUTION - DO NOT USE AVIATION GRADE GASOLINE

WINCH ASSY.

U.S. ARMY NO. 7538687

RATING 10,000 LBS. AT 15 FT. PER MIN. ON BARE DRUM

MANUFACTURER GARWOOD

SERIAL NO. 201856

POWER TAKE-OFF SHIFTS

HI
 NEU
 LOW
 NEU
 REV

CAUTION!

DO NOT TIGHTEN SAFETY BRAKE ADJUSTING BOLT MORE THAN NECESSARY TO HOLD LOAD

OFF IGNITION ON

START

DURABLACK PLATES \$5 ea

SERVICE AIR CLEANER ELEMENT WHEN RED INDICATOR IS IN UP POSITION

MANIFOLD HEATER SWITCH

ENGAGE HEATER WITH STARTER WHEN TEMPERATURE IS BELOW +20°F USE HEATER INTERMITTENTLY AT IDLE UNTIL ENGINE IS RUNNING SMOOTHLY

CAUTION: DO NOT ENGAGE HEATER UNLESS ENGINE IS BEING CRANKED

VEHICLE OPERATIONS CHECKLIST

1. Tires properly inflated
2. Windows clean
3. Mirrors adjusted
4. Passengers secure
5. Lights on
6. Drive defensively

CAUTION

PULL OUT DRUMLOCK BEFORE OPERATING WINCH

WARNING

DO NOT FORCE CLUTCH LEVER TO FREE DRUM CLUTCH, ENGAGE POWER TAKE OFF IN FORWARD OR REVERSE GEAR AS REQUIRED, AND SLIP ENGINE CLUTCH SLIGHTLY

WARNING

BUZZER OPERATION INDICATES THAT AIR SYSTEM PRESSURE IS BELOW SAFE OPERATING PRESSURE THE CAUSE OF LOSS OF AIR PRESSURE SHOULD BE DETERMINED IMMEDIATELY.

POWER TAKE-OFF AND WINCH OPERATION

WHEN WINCH IS USED TO ASSIST VEHICLE WITH WHEELS DRIVING THE POWER TAKE-OFF SHOULD BE IN LOW SPEED. THE TRANSMISSION IN LOW GEAR, AND THE TRANSFER CASE IN LOW RANGE.

YELLOW/BLACK \$8 ea

CAUTION

AFTER SHUT DOWN IN FREEZING TEMPERATURE DRAIN ALL WATER FROM FILTERS, TANKS, PUMPS, LINES, AND HOSES. LEAVE DRAIN VALVES OPEN. INSPECT UNIT TO INSURE ALL WATER HAS BEEN DRAINED

YELLOW/BLACK \$10 ea

M35A2 Dataplates Full Set \$120